



CONTACT

INNER: 6 FINGER CONTACT, IN HEAT TREATED BERYLLIUM COPPER
 FINISH: GOLD OVER 2-3 μ NICKEL OVER COPPER FLASH

OUTER SLEEVE

FINISH: 5 μ TIN OVER 2-3 μ INCKEL OVER COPPER FLASH

INSULATOR

GLASS FILLED POLYPHENLENE SULFIDE
 UL94V-0 RATED. (P.P.S.)

ELECTRICAL DATA

CONTACT RESISTANCE < 4 ml PER CONTACT
 INSULATION RESISTANCE > 10¹² QU-100V
 WORKING VOLTAGE: 10mv-60V

MECHANICAL DATA

TEMPERATURE RANGE: -55° C TO +155° C
 MECHANICAL LIFE CYCLE:
 1000 CYCLE INSERTIONS AND WITHDRAWALS
 WITH STEEL PIN 0.46mm

E			
D			
C			
B			
A	09-09-1998	6610P-321-19-109	Jerry Chen
REV	DATE	FILE	BY

DRAWN:	GENERAL TOLERANCE:
	±0.2
CHECKED:	UNIT: MM
	SCALE:
	SHEET: 1 / 1
	PROJECTION:

DESCRIPTION:	PGA PIN 321P
PART NO:	6610P-321-19-109

SIZE	A4
------	----